



Northstar Brand Rental Exclusive Power Equipment delivers premium quality and long-lasting performance. Suitable for professionals and homeowners, this equipment is easy to use and simple to maintain.

Available from Great Northern Equipment

CONCRETE | COMPACTION | GENERATORS | PRESSURE WASHERS | SPRAYERS | ACCESSORIES

POWER TROWEL IDEAL FOR LARGE JOBS

- Easy-to-use pitch and speed controls
- Worm reduction gear provides high torque at slower speed
- Safety stopper located on the handle grip allows for easy emergency shut down
- 36" diameter is ideal for big jobs like parking lots, driveways, and more
- Ring stationary guard for safety and protection
- 2-year limited warranty/3-year limited warranty on Honda GX engine
- Available to rental businesses only



ITEM #	ENGINE	BLADE DIAMETER	BLADES	HANDLE ADJUSTMENT	WEIGHT
49391.NOR	Honda GX160	36"	Four	0° - 15°	198 lbs

CONCRETE SCREED CONCRETE APPLICATIONS

- High-performance screed is reliable, durable choice for your concrete application
- Embeds aggregate and reduces air voids to product to strong, dense slab
- Design allows for single-person operation
- Screed boards sold separately (see below)
- 2-year limited warranty/3-year limited warranty on Honda GX engine
- Available to rental businesses only



ITEM #	ENGINE	VIBRATIONS PER MINUTE	BLADES
49163.NOR	Honda GX35	7,000	Aluminum Alloy Blades



SCREED BOARDS

ITEM #	DESCRIPTION
60849	4-1/2' Aluminum Board
49397	8' Aluminum Board
49398	10' Aluminum Board
49399	12' Aluminum Board
49400	14' Aluminum Board

PLATE COMPACTOR

FORWARD

- Ideal for compacting granular soils and crushed aggregate
- Float type carburetor
- Transistorized ignition
- Angled combustion chamber for increased power and efficiency
- Centrifugal flyweight type governor
- 12V lighting coil
- Gas tank strainer and antisplash device included
- Easy-check oil level for vibrating shaft (exciter) via sight glass
- Lift and protect guard applied
- 2-year limited warranty/3-year limited warranty on Honda GX engine
- Available to rental businesses only



ITEM #	ENGINE	FORCE	PLATE SIZE	TRAVEL SPEED	VPM
49160.NOR	Honda GX160	3,968 lbs	21-1/2" x 16-5/16"	65 - 82 ft/min	6,400

PLATE COMPACTOR

REVERSIBLE

- Efficiently compact sand, gravel, mixed soils
- Utilizes a hydraulic system to perform forward, reverse, and on-spot compaction
- Easily change direction with the control lever
- Heavy-duty shock mounts reduce vibration to the handle
- Wraparound protective cage has lift eye for easy transport
- 2-year limited warranty/3-year limited warranty on Honda GX engine
- Available to rental businesses only



ITEM #	ENGINE	FORCE	PLATE SIZE	COMPACTION	VPM
49162.NOR	Honda GX160	4,046 lbs	15-3/4" x 11-3/5"	5,000 sq ft/hour	6,000

PLATE COMPACTOR ACCESSORIES

ITEM #	DESCRIPTION
71184	Rubber Pad (Fits 49160)



TAMPING RAMMER

FOR NARROW JOBS

- Ideal for compacting cohesive soil in confined areas
- Covers 2,200 sq ft per hour
- Compaction depth up to 12"
- Durable bellows with low maintenance
- Convenient oil checking system and dual filter system
- Lightweight and well balanced for easy handling and operation
- Suitable for trenches, pipelines, and patching
- 2-year limited warranty
- Available to rental businesses only

POWERED by
HONDA



ITEM #	ENGINE	COMPACTION	PLATE SIZE	BEATS PER MINUTE
60369.NOR	Honda GXR120	3,814 lbs	11" X 13"	680 - 710 BPM

TAMPING RAMMER/ PLATE COMPACTOR FOR NARROW JOBS

- Ideal for narrow jobs with clay, sand, or gravel
- Easy-to-operate design allows access to narrow jobsites and makes turns with ease
- Combines tamping rammer and plate compactor functions
- Approximately 12" compaction depth, depending on soil
- Compacts 6,103 - 7,211 sq ft per hour
- Bore and stroke of 2.68" x 1.77"
- Design minimizes operator fatigue
- 2-year limited warranty/3-year limited warranty on Honda GX engine
- Available to rental businesses only

POWERED by
HONDA



**TWO PIECES
OF EQUIPMENT
IN ONE!**

ITEM #	ENGINE	FORCE	PLATE SIZE	COMPACTION
47016.NOR	Honda GX160	4,134 lbs	16.9" X 16.9"	6,400 VPM

GENERATORS ELECTRIC POWERED

- Digital CDI ignition offers excellent starting and high-power output
- Full roll cage with antirip mounts prevents damage if tipped
- Solid base prevents grass, dirt, and dust from getting into the engine and alternator
- V-mount vibration isolation system extends generator life
- High-quality 100% copper-wound head with low THD for safe use with sensitive equipment
- Includes voltmeter
- Optional wheel kits available (see below)
- Available to rental businesses only

POWERED by
HONDA



165601.NOR



165603.NOR



165604.NOR



165606.NOR



165607.NOR

ITEM #	ENGINE	WATTS	MAX AC OUTPUT	RATED AC OUTPUT	FUEL CAPACITY	RUN TIME/TANK (@ 50% LOAD)
165601.NOR	Honda GX270	5,500	56.5 - 63.3 Hz	4,500	6.5 Gal	14.5 Hours
165603.NOR	Honda GX390	8,000	56.5 - 63.3 Hz	6,600	6.5 Gal	10 Hours
165604.NOR	Honda GX390 (Electric Start)	8,000	56.5 - 63.3 Hz	6,600	6.5 Gal	10 Hours
165606.NOR	Honda GX630 (Electric Start)	13,000	56.5 - 63.3 Hz	10,500	11 Gal	10 Hours
165607.NOR	Honda GX690	15,000	56.5 - 63.3 Hz	13,500	11 Gal	8.5 Hours

GENERATOR ACCESSORIES

ITEM #	DESCRIPTION
165620	Wheel and Handles Kit (Fits 165601, 165603, 165604)
165621	Wheel and Handles Kit (Fits 165606, 165607)



WATER TANK

HEAVY-DUTY TRAILER WITH WATER TANK

- Corrosion-resistant poly tank with Hudson valve for easy filling
- 2" cam lock port allows quick-connection to water pumps
- Garden hose outlet for connecting to pressure washers
- Includes platform for mounting water pump, pressure washer, or other equipment
- 16" wheels with electric brakes and protective fenders
- 2,000 lbs A-Frame jack for optimum performance
- 2-5/16" bolt-on coupler hitch with safety cables to keep the trailer secure
- Break-away switch activates the brakes if vehicle and trailer disconnect
- Trailer lights for safe towing
- Available to rental businesses only



ITEM #	TANK	FRAME	DIMENSIONS	WEIGHT
999889	600 Gallon Poly	Grade 50 Steel	138"L x 85"W x 80"H	1,200 lbs

COLD WATER PRESSURE WASHERS

GAS POWERED

- Great for lawn and garden cleaning, heavy-duty machinery, driveways, parking lots, patios, buildings, and more
- 10" flat free tires for easy portability
- Oil drain cutouts for quick oil changes
- Easy start prevents pressure buildup for smoother, easier recoil pulling
- 3-year limited warranty on Honda engine, 5-year limited warranty on pump, 10-year limited warranty on frame
- Available to rental businesses only

POWERED by
HONDA



157132.NOR

157133.NOR



157122.NOR



157124.NOR



157127.NOR



157136.NOR

ITEM #	ENGINE	PUMP	PRESSURE	FLOW	SPRAY GUN	FRAME	MAX TEMP
157132.NOR	Honda GX200	CAT 4DNX	3,300 PSI	2.5 GPM	Rear Entry w/ Lance	1-1/4" Aluminum	140°
157133.NOR	Honda GX390	CAT 66DX	4,200 PSI	3.5 GPM	Industrial Rear Entry	1-1/4" Aluminum	140°
157122.NOR	Honda GX160	Comet DWD	3,100 PSI	2.5 GPM	Rear Entry w/ Lance	1-3/8" Steel	140°
157124.NOR	Honda GX270	CAT 4SPX	3,600 PSI	3.0 GPM	Industrial Rear Entry w/ Lance	1-3/8" Steel	140°
157127.NOR	Honda GX390	CAT 66DX	4,200 PSI	3.5 GPM	Industrial Rear Entry w/ Lance	1-3/8" Steel	140°
157136.NOR	Honda GX390	CAT 5CP Belt Drive	4,000 PSI	3.5 GPM	Industrial Rear Entry	1-3/8" Steel	140°

HOT WATER PRESSURE WASHERS

GAS POWERED

- Innovative digital thermostat provides far superior temperature regulation compared to other brands
- Downdraft burner with seamless coil provides consistent heat and up to 35% increased fuel efficiency
- 2-year limited warranty on frame; 3-year limited warranty on Honda engine; 5-year limited warranty on pump; 5-year limited warranty on heat exchanger
- Available to rental businesses only

POWERED by
HONDA



157114.NOR



157115.NOR

ITEM #	ENGINE	PUMP	PRESSURE	FLOW	SPRAY GUN	MAX TEMP
157114.NOR	Honda GX200	Comet DWD	2,700 PSI	2.5 GPM	Rear Entry w/ Lance	250°
157115.NOR	Honda GX390	CAT 66DX	3,000 PSI	4.0 GPM	Industrial Rear Entry	250°

HOT WATER PRESSURE WASHER

TOWABLE - GAS POWERED

- Innovative digital thermostat provides far superior temperature regulation compared to other brands
- Downdraft burner with seamless coil provides consistent heat and up to 35% increased fuel efficiency
- 2-year limited warranty on frame; 3-year limited warranty on Honda engine; 5-year limited warranty on pump; 5-year limited warranty on heat exchanger
- Available to rental businesses only



200
GALLON
TANK



POWERED by
HONDA



ITEM #	ENGINE	PUMP	PRESSURE	FLOW	SPRAY GUN	MAX TEMP
157595.NOR	Honda GX630	CAT 66DX	4,000 PSI	4.0 GPM	Industrial Rear Entry w/ Lance	250°

PRO SHOT PRESSURE WASHERS

GAS POWERED

- General Pump® heavy-duty triplex pump
- Five cleaning modes from cold water to 250°F wet steam to handle any job
- Two, 24 gallon chemical tanks can be used individually or combined
- Onboard 2000 watt generator with 100% copper-wound head and automatic voltage regulation
- Self-cleaning inlet filter prevents debris from entering the pump
- Easy access to vital burner components simplifies servicing
- Heavy-duty A-frame trailer
- Built-in tool box fits two 5-gallon buckets
- Available to rental businesses only



157563.NOR



157565.NOR



157569.NOR



ITEM #	ENGINE	WATER TANK	PUMP	PRESSURE	FLOW	SPRAY GUN	MAX TEMP
157563.NOR	Kohler ECH630 EFI	400 Gal	Triplex	4,000 PSI	5.5 GPM	Industrial w/ Lance	250°
157565.NOR	Kohler ECH749 EFI	600 Gal	Triplex	3,000 PSI	8.0 GPM	2 Industrial w/ Lance	250°
157569.NOR	Kubota D902 Diesel	400 Gal	Triplex	4,000 PSI	5.5 GPM	Industrial w/ Lance	250°

BROADCAST AND SPOT SPRAYERS

ELECTRIC POWERED

- 100% continuous-duty rating
- Large capacity propriety tank design features extra-thick walls that are UV-resistant and compatible with virtually all pesticides
- Spring-loaded, breakaway boom arms fold away for compact storage
- Easy to empty tank with bottom drain
- Includes pressure gauge and remote switch with battery clamps
- Attaches to ATV or garden tractor
- Available to rental businesses only

282780.NOR



282785.NOR



282585.NOR



99905.NOR



99906.NOR



99907.NOR



ITEM #	POWER SUPPLY	TYPE	TANK SIZE	PRESSURE	FLOW	PATTERN
282780.NOR	12V	Tow-Behind	21 Gal	70 PSI	2.2 GPM	Cone/Stream
282785.NOR	12V	Tow-Behind	31 Gal	70 PSI	2.2 GPM	Cone/Stream
282585.NOR	12V	Tow-Behind	41 Gal	60 PSI	4.0 GPM	Cone/Stream
99905.NOR	12V	ATV Boomless	16 Gal	70 PSI	2.2 GPM	Cone/Stream
99906.NOR	12V	ATV Boomless	26 Gal	70 PSI	2.2 GPM	Cone/Stream
99907.NOR	12V	ATV Boomless	26 Gal	60 PSI	5.5 GPM	Cone/Stream